

ATI Tyre Inflator

The latest addition to PCL's mechanical inflator range.

PCL's latest value mechanical tyre inflator, the ATI is suitable for tyreshops, garages, car dealers and transport depots. Featuring a simple user-friendly dial display enabling operators to provide fast, safe, cost-effective and accurate tyre inflation, which in turn means tyre users can reap the rewards of extended tyre life, increased fuel economy and improved safety.

Key features

- Clear dial display
- Modern, lighter weight design
- Includes a metal inlet as standard
- Direct valve design increasing inflation and deflation rates
- Individually tested and certified
- Built in swivel and hanging device
- Psi / Bar

Specifications

Pressure Measurement

Reading Accuracy: 0.1 bar / 2 psi
 Max Inlet Pressure: 15 bar/ 218 psi
 Inflation Range: 0-12 bar/ 170 psi

Inflation Speeds

Inflation flow: Max 910 l/min @ 13 bar supply

Compliance

For an EC Directive 86/217/EEC approved product, please use premium approved, robust, reliable and long life AirForce II Dial Tyre Inflator (AFG1).

www.pclairtechnology.com



Part No.	Hose Length	Tyre Valve Connection
ATIH08	1.8 m	Euro clip-on
ATIH081	0.5 m	Euro clip-on