

DRIVEN BY AIR.



Compressor Accessory Kit



This Compressor Accessory Kit comes complete with some of PCL's popular workshop equipment ideal for low volume tyre inflation, light viscosity painting application or other semi-professional and DIY workshop applications.

The kit contains genuine PCL couplings and adaptors allowing the user to connect to an existing air line or compressor supply with ease.

Kit Contains

- x1 Compressor Kit Box
- x1 AC21CF Airflow Coupling Female Rp 1/4
- x3 ACA2593 Standard Adaptor Male R 1/4
- x1 ACA2746 Standard Adaptor Female Rp 1/4
- x1 LTG01 Blowgun Style Tyre Inflator
- x1 SG02L Lite Gravity Spray Gun
- x1 BG5002 Blowgun Conical Nozzle
- x1 HA5201 Nylon Hose

www.pclairtechnology.com

A HORNGROUP BRAND

Features & Benefits

Blowgun Style Tyre Inflator

- Simple and easy to use
- Ideal for general low volume tyre inflation

Lite Gravity Spray Gun

- Ergonomic design for comfort
- Lightweight materials
- Ready for immediate use
- Comes complete with cleaning brush and hose tailpiece adaptor

Blowgun Conical Nozzle

- Ergonomically designed handle, for comfort in use
- Valve allows trigger-adjustable airflow
- Supplied in blister pack

Nylon Hose

- Nylon Material
- Nickel plated 360° swivel fittings
- 200 m straight ends with spring guard

Airflow Coupling

- Compatible with the Standard Adaptor
- Positive locking mechanism

Standard Adaptors

- Case hardened for longer life
- Used with Airflow, Vertex, Twin, non-corrodible and Safeflow Safety couplings

Specification

Part No. GCK01

Blowgun Style Tyre Inflator

Tyre Valve Connection: Euro Clip-on

Hose Length: 0.4m

Calibration: 0-174 psi / 0-12 bar

Lite Gravity Spray Gun

Tank Capacity: 600 cc

Operating Pressure: 3 - 4 bar

Air Consumption: 4.2 - 7.1 cfm

Nozzle Style: 1.5 mm

Pattern Width: 120 - 250 mm

Body & Cannister Material: Aluminium & Plastic

Blowgun Conical Nozzle

Maximum Supply Pressure: 10 bar / 140 psi

Connection: 1/4 Female

Air Flow: 270 l/min / 9.3 cfm

Temperature Range: 0 to 80 °C

Grip Style: Pistol

Nozzle Style: Conical

Nylon Hose

Hose Length: 7.6 m

Hose Inside Diameter: 6 mm

Hose Outside Diameter: 8mm

Fittings: R 1/4 Swivel ends

Maximum Working Pressure: 200 psi / 14 bar

Airflow Coupling

Nominal Bore: 4.8 mm

Maximum Flow Rate: 43 cfm @ 100 psi supply

Maximum Working Pressure: 200 psi / 14 bar

Standard Adaptors

Nominal Bore: 4.8 mm